

Super Night Vision Camera

High Resolution IR Dome Camera

SN-FXP0580GIR

Vandal Resistant Varifocal IR Dome Camera

SN-FXP0580DIR

Key Features

- 1/3" SONY SUPER HAD II CCD, 540TVlines
- 15m IR Visible Range
- Min.Illumination: 0Lux (IR LED ON)
- AGC, ATW, BLC
- Tool-free 3-Axis
- 12VDC Power Supply



SN-FXP0580GIR




SN-FXP0580DIR



Specifications

Model	SN-FXP0580GIR	SN-FXP0580DIR
Image Sensor	1/3" SONY SUPER HAD CCD	
Signal System	PAL /NTSC	
Effective Pixels	PAL: 752 (H)×582 (V); NTSC: 768 (H)×494 (V)	
Resolution	540TVlines	
Min.Illumination	0Lux (IR LED ON)	
S/N Ratio	50dB	
ES	1/50~1/100,000/sec (PAL), 1/60~1/100,000/sec (NTSC)	
White Balance	Auto	
AGC	Auto	
BLC	ON/OFF	
Gamma Correction	0.45	
Sync.mode	Internal	
Lens	Vari-focal Lens f=4-9mm 2.6-6mm (Optional)	
IR LED	850nm	
IR Beam Distance	10-15m	
IR LED Control	ON: 1~3Lux; OFF: 5~6Lux	
Video Output	1.0Vp-p, 75Ohm	
Power Supply	DC12V	
Power Consumption	320mA (Max.)	
Operation Temperature	-10 ~ +50 RH90% MAX (non-condensing)	
Dimension	φ 150×127mm	
Weight	1300g	


Dimension (Unit: mm)



SN-FXP0580GIR



SN-FXP0580DIR



Model Numbers

Model	SN-FXP0580GIR/V/10 SN-FXP0580DIR/V/10	SN-FXP0580GIR/V/20 SN-FXP0580DIR/V/20
Power Supply	DC12V, 50Hz	DC12V, 60Hz
Signal System	PAL	NTSC
Lens	Vari-focal Lens f=4-9mm 2.6-6mm,2.8-11mm (Optional)	