

SN-WP687PTA/30W



Outdoor Speed Dome Camera

- 0~360° Endless Pan, 0~180° Tilting (D-Flip)

- Pan/Tilt Speed Min. 0.4°/sec, Max. 270°/sec

- Preset 220 ea, Auto Pan 4 ea, Pattern 4 ea

Features

- 1/4" SONY CCD
- 0~360° Endless Pan, 0~180° Tilting (D-Flip)
- Pan/Tilt Speed Min. 0.4°/sec, Max. 270°/sec
- Preset 220 ea, Auto Pan 4 ea, Pattern 4 ea
- Day Night Function (ICR)
- Back Light Compensation
- Privacy Mask Function
- Time & Day Scheduling
- CCVC (Camera Control Via Coaxial cable, Controller : SN-CC50)
- RS-485(Multi-Protocol support)
- Multi-Language OSD support
- Alarm Input 7 ea, Output 2 ea
- Operating Temp. : -40 ~ 60°C

Specifications

MODEL	SN-WP687PTA/30W
Camera	
Signal System	PAL /NTSC
Image Sensor	1/4" Ex-View HAD CCD (SONY)
Day & Night	Yes, with Removable IR-Cut Filter
Minimum Illumination	0.04Lux
Active Pixel	PAL: 752(H)×582(V); NTSC: 768(H)×494(V)
Horizontal Resolution	540Lines
Focus Length	3.5mm~105mm
Zoom Ratio	30X Optical zoom, With auto focus (16X digital zoom)

Function	
Panning Angle	360°Continuous rotation
Tilt Angle	0°~90°
Preset	220 Positions
Pattern	4 Patterns
Tour	6 Guard tours
Auto Scan	4 Groups
Resistance Fog Function	Yes
English/ Chinese Menu	Available
Real-time Clock Function	Available
Inside Temperature Display	Available
Rotation speed	0.4°~270°/sec(Pan); 0.4°~160°/sec(Tilt)
Alarm Input/Output	7 input,2 relay output
Working Temperature	-40°C -+60°C
Power Supply	24VAC/2A
Power Consumption	15W(Indoor)

